

## Belt Drive and Blower Applications

**Features:** Class "B" Ins. • Continuous Duty • Energy Efficient \$ (see notes) • Open and TEAO  
 • Reversible • Sleeve & Ball Bearing • 60 HZ (50 HZ per notes)



SGK2034

### SPLIT PHASE - NEMA AND UNITY SERVICE FACTOR

HP	RPM	F.L.			Frame	Stock Number	Bearings	Protector	Approx. "C"	Dim. "AG"	Enclosure	Conn. Dia.	Notes
		Volts	Amps	S.F.									
1/3-1/10	1725/1140	115	6.7/3.3	1.35	56Z	SGF2034V1	Sleeve	Auto	9.9	8.3	Open	105	5,10
		115	6.7/3.3	1.35	56	SGK2034	Sleeve	Auto	10.3	8.4	Open	105	5
1/2	1725	115	5.7	1.25	48/56	SC6054A	Sleeve	Auto	9.9	8.0	Open	104	1,3
		115	7.2	1.25	48/56	GF2054	Sleeve	Auto	9.9	8.0	Open	39	1
		115	7.2	1.25	56	GK2054	Sleeve	Auto	9.9	8.0	Open	39	
		115/230	7.2/3.6	1.25	48/56	GF2054D	Sleeve	Auto	9.9	8.0	Open	38	1
		115/208-230	7.2/3.6	1.25	48/56	BF2054	Ball	Auto	9.9	8.0	Open	38	1,7
		115/230	7.6/3.8	1.00	56	ARS2050D	Sleeve	Auto	10.8	8.6	TEAO	38	2
		115/230	9.0/4.5	1.25	56	RS2054D	Sleeve	Auto	10.0	8.1	Open	38	9
		115/230	8.8/4.4	1.25	56	RB2054D	Ball	Auto	10.0	8.1	Open	38	7
1/2-1/6	1725/1140	115	9.0/4.5	1.35	56Z	SGF2054VI	Sleeve	Auto	10.0	8.3	Open	105	10,5
1/2-1/4	1725/1140	115	9.0/6.3	1.25	56	SGK2054	Sleeve	Auto	10.8	8.9	Open	105	5
3/4	1725	115	10.9	1.25	56	GK2074	Sleeve	Auto	10.8	8.9	Open	39	
		115/230	11.0/5.5	1.25	56	GK2074D	Sleeve	Auto	10.8	8.9	Open	38	
		115	7.8	1.25	56	SC6074A	Sleeve	Auto	11.3	9.4	Open	104	3
1	1725	115/230	13.6/6.5	1.15	56	GK2104D	Sleeve	Auto	12.3	10.4	Open	38	

**Notes:**

- 1. 48/56 FR = 1/2" x 1.5" Shaft with 5/8" shaft adapter - 48/56 slotted 3" height base
  - 2. TEAO gasketed conduit box - 3/4" extended thru bolts
  - 3. Energy efficient \$ - split phase start/capacitor run
  - 5. 2-speed
  - 7. 1/2" extended thru bolts, shaft end
  - 9. Suitable for 208V at 1.0 S.F.
  - 10. 56Z = 1/2" flatted shaft.
- See page 159 for mounting dimensions