

Special Unit Bearing Replacement Motors

Ice-O-Matic



225, 227



246, 254, 256



260

Stock No.	Watt Output	Volts	RPM	Amps	Rot. S.E.	Speeds	Capacitor	Motor Dia.	"A" Dim	Diameter & Length	Cross Reference	Notes
225	6W	115	1550	.36	CWLE	1	Shaded Pole	3-1/2"	2.78	1/4"-20 THD.	332418-011	
227	9W	115	1550	.58	CWLE	1	Shaded Pole	3-1/2"	2.78	1/4"-20 THD.	332417-011	
246	16W	115	1550	.80	CWLE	1	Shaded Pole	3-7/8"	3.39	1/4"-20 THD.	9161045-04	
254	35W	115	1550	1.4	CWLE	1	Shaded Pole	3-7/8"	3.39	1/4"-20 THD.	9161078-01	
256	35W	230	1550	.70	CWLE	1	Shaded Pole	3-3/8"	3.39	1/4"-20 THD.	9161078-03 309316-000	
260	50W	230	1500	.85	CWLE	1	Shaded Pole	3-7/8"	3.50	3/8" x 1-1/2"	319357-000	

IMI Cornelius



293, 294



297



225, 227



256



260, 291

Stock No.	Watt Output	Volts	RPM	Amps	Rot. S.E.	Speeds	Capacitor	Motor Dia.	"A" Dim	Diameter & Length	Cross Reference	Notes
225	6W	115	1550	.36	CWLE	1	Shaded Pole	3-1/2"	2.78	1/4"-20 THD.	332418-011	
227	9W	115	1550	.58	CWLE	1	Shaded Pole	3-1/2"	2.78	1/4"-20 THD.	332417-011	
293	15W	115	1500	.60	CCWLE	1	Shaded Pole	3-7/8"		5/16"-7" THD.	31-0472 30-9369	
294	15W	115	1500	.60	CCWLE	1	Shaded Pole	3-7/8"		5/16"-5" THD.	18-7036 18-7388 18-9840	
297	25W	115	1500	1.1	CCWLE	1	Shaded Pole	3-7/8"		5/16" x 7	31-0154	1
256	35W	230	1500	.70	CWLE	1	Shaded Pole	3-7/8"	3.38	1/4"-20 THD.	30-9316	
291	50W	115	1500	1.7	CWLE	1	Shaded Pole	3-7/8"	3.80	5/16" x 3	13435-0000	
260	50W	230	1500	.85	CWLE	1	Shaded Pole	3-7/8"	3.50	3/8" x 1-1/2"	319352-000	

Kelvinator



277

Stock No.	Watt Output	Volts	RPM	Amps	Rot. S.E.	Speeds	Capacitor	Motor Dia.	"A" Dim	Diameter & Length	Cross Reference	Notes
277	15W	115	1500	.60	CCW	1	Shaded Pole	3-7/8"	3-1/8	5/16 x 7-1/2	5.024-0366	

Larkin Coil



277

Stock No.	Watt Output	Volts	RPM	Amps	Rot. S.E.	Speeds	Capacitor	Motor Dia.	"A" Dim	Diameter & Length	Cross Reference	Notes
277	15W	115	1500	.60	CCW	1	Shaded Pole	3-7/8"	3-1/8	5/16 x 7-1/2	24-0366	

Notes:

- Pinhole in shaft
 - *Rotation Determined by Viewing Lead End
- See Page 150 for Parts & Accessories