

- Features:** Class "B" Insulation • High Start Torque
 • Open Construction • Reversible • Sleeve & Ball Bearing
 • 2, 4 and 6 Pole • 40° C Ambient • 60 HZ • Volts at 1.0 S.F




BK1054



RB1054A

HP	RPM	Volts	F.L. Amps	S.F.	Frame	Stock Number	Equivalent	Bearings	Protector	Approx. "C"	Dim. "AG"	Enclosure	Conn. Dia.	Notes
3/4	3450	115/208-230	8.8/4.4	1.25	48	RBF1072A		Ball	Auto	10.4	8.5	Open	38	
		115/208-230	10.0/5.0	1.5	48	BF1072		Ball	Auto	11.1	9.2	Open	22	5,6,7,8
		115/208-230	10.0/5.0	1.5	56	BK1072		Ball	Auto	11.6	9.4	Open	22	5,6,7,8
		115/230	11.2/5.6	1.25	56	RB1072A		Ball	Auto	11.3	9.1	Open	38	
	1725	115/208-230	12.0/6.0	1.25	56	BK1074		Ball	Auto	12.7	10.7	Open	22	5,6,7,8
		115/208-230	11.6/5.8	1.25	56	RB1074A		Ball	Auto	11.3	9.1	Open	38	
		115/230	13/6.5	1.00	56	RS1070A		Sleeve	Auto	11.3	9.1	Open	38	
		115/230	10.4/5.20	1.25	56	RS1074		Sleeve	None	11.8	9.6	Open	101	
		115/230	10.4/5.20	1.25	56	RS1074A		Sleeve	Auto	11.8	9.6	Open	38	
1	3450	115/208-230	12.6/6.3	1.4	48	BF1102		Ball	Auto	11.6	9.7	Open	22	5,6,7,8
		115/208-230	12.6/6.3	1.4	56	BK1102		Ball	Auto	11.9	9.7	Open	22	5,6,7,8
		115/230	11/5.5	1.25	48	RBF1102A		Ball	Auto	10.9	9.0	Open	38	
		115/230	12.2/6.1	1.25	56	RS1102A		Sleeve	Auto	11.8	9.6	Open	38	
		115/230	12.2/6.1	1.25	56H	RB1102A		Ball	Auto	11.4	9.2	Open	38	
	1725	115/208-230	14/7.0	1.25	56	BK1104	RB1104A	Ball	Auto	13.7	11.5	Open	22	5,6,7,8,9
		115/230	14.2/7.1	1.25	56H	RS1104A		Sleeve	Auto	11.8	9.6	Open	38	
		115/230	14.2/7.1	1.15	56	RB1104		Ball	None	11.8	9.6	Open	101	
		115/230	14.2/7.1	1.25	56	RB1104A		Ball	Auto	11.4	9.2	Open	38	
		115/230	14.2/7.1	1.25	56H	RS1104A		Sleeve	Auto	11.8	9.6	Open	38	
1-1/2	3450	115/208-230	17.2/8.6	1.3	56H	BK1152		Ball	Auto	13.7	11.5	Open	22	5,6,7,8
		115/230	16.4/8.2	1.2	56	RB1152A		Ball	Auto	11.8	9.6	Open	38	
	1725	115/208-230	16.4/8.2	1.2	56H	RB1154A		Ball	Auto	12.8	10.6	Open	38	
		115/208-230	19.0/9.5	1.15	56H	BK1154	RB1154A	Ball	Auto	14.7	12.5	Open	22	5,6,7,8,9
2	3450	115/208-230	24.6/12.3	1.2	56	RB1202A		Ball	Auto	12.8	10.6	Open	38	
		115/208-230	21.2/10.6	1.2	56H	BK1202		Ball	Auto	14.2	12.0	Open	22	5,6,7,8
	1725	115/208-230	24.6/12.3	1.15	56	RB1204A		Ball	Auto	12.8	10.6	Open	38	
		115/208-230	25/12.5	1.15	56H	BK1204	RB1204A	Ball	Auto	15.3	13.1	Open	22	5,6,7,8,9

- Notes:**
 5. Sealed switch design
 6. Start capacitor inside
 7. Terminal board
 8. Moderate start torque
 9. Disc. when stock is depleted
 See page 159 for mounting dimensions.



Shaft Dimensions
 48 = 1/2" Flat x 1-5/8"
 56 = 5/8" Keyed x 1-7/8"
 56H = 5/8" Keyed x 1-7/8"