

Compressors, Pumps, Blowers, Conveyors, Industrial Duty

- Features:** Capacitor Start • Class "B" Ins. • High Start Torque
- Open Drip Proof • Reversible • Rigid Base • Sleeve & Ball Bearing
 - Suitable for 208 Volts at 1.0 S.F. • 40° C Ambient • 60 HZ




OB1104

ODP, RIGID BASE, SINGLE PHASE CAPACITOR START

HP	RPM	Volts	F.L. Amps	S.F.	Frame	Stock Number	Bearings	Protector	Approx. "C"	Dim. "AG"	Conn. Dia.	Notes
1/4	1725	115/230	5.4/2.7	1.35	48	OS1024	Sleeve	None	9.4	7.5	101	
		115/230	5.4/2.7	1.35	48	OB1024	Ball	None	9.4	7.5	101	
1/3	1725	115/230	6.1/3.1	1.35	56	OB1034	Ball	None	10.2	8.0	101	
		115/230	5.6/2.8	1.35	56	OB1034A	Ball	Auto	9.8	7.6	38	
		115/230	6.4/3.2	1.35	56	OS1034	Sleeve	None	9.8	7.6	101	
		115/230	5.6/2.8	1.35	56	OS1034A	Sleeve	Auto	9.8	7.6	38	
		115/230	8.8/4.4	1.25	56	OS1054	Sleeve	None	10.8	8.6	101	
1/2	1725	115/230	8.8/4.4	1.25	56	OS1054A	Sleeve	Auto	10.8	8.6	38	
		115/230	8.8/4.4	1.25	56	OB1054	Ball	None	10.8	8.6	101	
		115/230	8.8/4.4	1.25	56	OB1054A	Ball	Auto	10.8	8.6	38	
		115/230	10.4/5.2	1.25	56	OS1074	Sleeve	None	11.8	9.6	101	
3/4	1725	115/230	10.4/5.2	1.25	56	OS1074A	Sleeve	Auto	11.8	9.6	38	
		115/230	10.4/5.2	1.25	56	OB1074	Ball	None	11.8	9.6	101	
		115/230	10.4/5.2	1.25	56	OB1074A	Ball	Auto	11.8	9.6	38	
		115/230	10.4/5.2	1.25	56	OB1074M	Ball	Man	11.8	9.6	38	
		115/230	15.4/7.7	1.15	56H	OB1104	Ball	None	12.3	10.1	101	
1	1725	115/230	15.4/7.7	1.15	56H	OB1104A	Ball	Auto	12.3	10.1	38	
		115/230	15.4/7.7	1.15	143T	OB1104T	Ball	None	12.7	10.1	101	
		115/230	20.0/10.0	1.15	56H	OB1154	Ball	None	12.3	10.1	101	
1-1/2	1725	115/230	20.0/10.0	1.15	56H	OB1154A	Ball	Auto	13.3	11.1	38	
		115/230	20.0/10.0	1.15	145T	OB1154T	Ball	None	13.2	10.6	101	
		115/230	26.0/13.0	1.15	56H	OB1204	Ball	None	13.7	11.5	36	
2	1725	115/230	26.0/13.0	1.15	56H	OB1204A	Ball	Auto	13.7	11.5	37	
		115/230	26.0/13.0	1.15	145T	OB1204T	Ball	None	14.5	11.9	36	3

Note:
3. Base 56H.
See page 159 for mounting dimensions.



Shaft Dimensions
 48 = 1/2" Flat x 1-5/8"
 56 = 5/8" Keyed x 1-7/8"
 56H = 5/8" Keyed x 1-7/8"
 143T/145T = 7/8" Keyed x 2-1/4"