

# Century® Fan and Blower Motors • Three Phase

## Heating, Ventilating & Air Conditioning Blower Motors • Dripproof • Cushion & Rigid Base • 3600 & 1800 RPM • 1/2 thru 10 HP

**Features:** Ball Bearings • 60 Hz • 40°C Ambient • Class A or B Insulated • Quick-Connect Design Bracket, 56 Frame only • 56, 56H and 56HZ Mounting Provisions • Reverse Ventilation for Superior Motor Cooling



H853

HP	RPM	Volts	Frame	Base	Overload Protector	Service Factor	Full Load Amps	Eff.	Insul. Class	Stock Number	"C" Dim.	Notes		
1/2	3600	460/200-230	56	Resilient	Auto	1.60	1.0/1.9-2.0		B	H840	12.19			
		460/200-230	56	Resilient	Auto	1.25	1.5/2.5-3.0		B	H850	12.19			
	1800	575	56	Resilient	Auto	1.25	.70		B	H940	12.19			
		575	56	Resilient	None	1.25	.88		A	H957	9.82			
		460/200-230	56	Rigid	Auto	1.25	1.5/2.5-3.0		B	H880	12.19			
3/4	3600	460/200-230	56	Resilient	Auto	1.50	1.4/2.8-2.8		B	H841	12.69			
		460/200-230	56	Resilient	Auto	1.25	1.7/2.9-3.4		B	H851	12.19			
	1800	575	56	Resilient	Auto	1.25	.90		B	H941	12.19			
		575	56	Resilient	None	1.25	1.0		A	H958	10.07			
		460/200-230	56	Rigid	Auto	1.25	1.7/2.9-3.4		B	H881	12.19			
1	3600	460/200-230	56H	Resilient	Auto	1.40	1.8/3.5-3.6		B	H842	12.69			
		575	56H	Resilient	Auto	1.40	1.5		B	H950	12.69			
	1800	460/200-230	56H	Resilient	Auto	1.15	1.9/3.5-3.8		B	H852	12.67			
		460/200-230	56HZ	Resilient	Auto	1.15	1.9/3.5-3.8		B	H888	12.56			
		575	56H	Resilient	Auto	1.15	1.5		B	H942	12.67			
		575	56	Resilient	None	1.25	1.4		B	H959	11.07			
		460/200-230	56H	Rigid	Auto	1.15	1.9/3.5-3.8		B	H882	12.69			
		460/200-230	56HZ	Rigid	Auto	1.15	1.9/3.5-3.8		B	H883	12.56			
1-1/2	3600	460/200-230	56H	Resilient	Auto	1.30	2.3/4.7-4.6		B	H843	12.94			
		460/200-230	56H	Rigid	Auto	1.30	2.3/4.7-4.6		B	H756	12.94			
	1800	575	56H	Resilient	Auto	1.15	1.8		B	H944	12.94			
		460/200-230	56H	Resilient	Auto	1.15	2.8/5.0-5.6		B	H853	12.94			
		208-230/460	56HZ	Resilient	Auto	1.15	4.8-4.8/2.4		B	H048	13.06			
		575	56	Resilient	Auto	1.20	2.0		B	H943	12.94			
		575	56H	Resilient	None	1.20	2.0		B	H960	12.19			
		460/200-230	56H	Rigid	Auto	1.15	2.8/5.0-5.6		B	H884	12.94			
		460/200-230	56HZ	Rigid	Auto	1.15	2.8/5.0-5.6		B	H885	12.81			
		575	56HZ	Rigid	Auto	1.20	2.0		B	H951	12.69			
2	3600	460/200-230	56H	Resilient	Auto	1.20	2.9/6.0-5.8		B	H844	13.94			
		575	56H	Resilient	Auto	1.20	2.4		B	H952	13.94			
	1800	460/200-230	56HZ	Resilient	Auto	1.15	3.5/6.6-7.0		B	H854	13.81			
		460/200-230	56HZ	Rigid	Auto	1.15	3.5/6.6-7.0		B	H886	13.81			
		575	56HZ	Rigid	Auto	1.20	2.4		B	H953	13.06			
3	3600	460/200-230	56HZ	Resilient	Auto	1.15	4.3/9.0-8.6		B	H845	13.81			
		460/200-230	56HZ	Rigid	Auto	1.15	4.3/9.0-8.6		B	H757	13.81			
		575	56HZ	Resilient	Auto	1.15	3.6		B	H954	14.21			
	1800	208-230/460	56Y	Rigid	Auto	1.15	10.6/4.8		B	H980	14.96	1		
		460/200-230	56HZ	Resilient	Auto	1.15	4.4/9.0-8.8		B	H855	14.56			
		460/200-230	56HZ	Rigid	Auto	1.15	4.4/9.0-8.8		B	H887	14.56			
		575	56HZ	Rigid	Auto	1.15	3.6		B	H955	14.56			
		575	56HZ	Resilient	Auto	1.15	3.6		B	H1021	14.56			
		5	3600	460/208-230	56HZ	Rigid	Auto	1.15	6.6/13.4-13.2		B	H847	15.06	3
				575	56HZ	Rigid	Auto	1.15	5.4		B	H956	15.06	
1800	200-208		184T	Rigid	Auto	1.15	16.0-16.0	84.0	B	R239	14.09			
	208-230/460		56Y	Rigid	None	1.15	15.0/7.4		B	H979	15.93	2		
	230/460		184T	Rigid	Auto	1.15	14.6/7.3	84.0	B	R234	14.09			
7-1/2	1800	230/460	213T	Rigid	Auto	1.15	19.0/9.5	88.5	B	R333	17.57			
10	1800	230/460	215T	Rigid	Auto	1.15	25.0/12.5	88.5	B	R331	16.57			

**Notes:**

1. Carrier replacement for HD60FK651, Special "BA" Dim. = 4.12"
2. Carrier replacement for HD60FK652, Special "BA" Dim. = 4.12"
3. Open motor construction, overload protector mounted at 12 o'clock