



Squirrel Cage • Dripproof • Standard, EPAct CC001A (E-Plus[®]) and Premium (E-Plus[®] 3) Efficiency • Cushion and Rigid Base • 3600, 1800 and 1200 RPM • 1/4 thru 400 HP























E226

Features: Ball Bearings • 60 Hz • 40°C Ambient • Class B or F Insulated • NEMA Service Factor • Continuous Duty • NEMA Design B • E-Plus Motors meet the requirements of the Energy Policy Act of 1992. E-Plus 3 motors exceed the requirements of the Energy Policy Act of 1992



Motors specially designed, tested and warranted to be **Corona-Free** for compatible inverter duty are marked on this page with a  or footnote 5 or 6.

Applications: Pumps, fans, compressors, conveyors

HP	RPM	Volts	Frame	Cast Iron	Base	Efficiency	Service Factor	Full Load Amps	Insul. Class	Stock Number	"C" Dim.	Notes		
1-1/2	3600	200-230/460	56		Cushion		1.30	4.5-4.2/2.1	B	H531	11.07			
		200-230/460	143T		Rigid	82.5	1.15	4.2-4.0/2.0	B	E1010	13.06	5 S		
		460/200-230	56H		Cushion		1.30	2.3/4.7-4.6	B	H843	12.94	1,2		
		460/200-230	56H		Rigid		1.30	2.3/4.7-4.6	B	H756	12.94	1,2		
	1800	3600	575	56H		Cushion		1.15	1.8	B	H944	12.94	2	
			200	145T		Rigid	84.0	1.15	4.5	B	E104 	13.81	5 S	
		1800	200-230/460	56H		Cushion		1.20	5.0-5.0/2.5	B	H536	12.19		
			200-230/460	56H		Rigid		1.20	5.0-5.0/2.5	B	H534	12.19		
			200-230/460	145T		Rigid		1.15	5.0-5.0/2.5	B	R110	12.56	7	
			200-230/460	145T		Rigid	84.0	1.15	4.5-3.9/1.95	B	E101 	13.81	5 S	
			230/460	145T		Rigid	85.5	1.15	4.6-4.0/2.0	B	E1016 	14.56	6 S	
			208-230/460	56HZ		Cushion		1.15	4.8-4.8/2.4	B	H048	13.06	1,2	
460/200-230			56H		Cushion		1.15	2.8/5.0-5.6	B	H853	12.94	1,2		
460/200-230			56H		Rigid		1.15	2.8/5.0-5.6	B	H884	12.94	1,2		
460/200-230			56HZ		Rigid		1.15	2.8/5.0-5.6	B	H885	12.81	1,2		
575			56		Cushion		1.20	2.0	B	H943	12.94	2		
575			145T		Rigid	84.0	1.15	1.56	B	E1007 	14.56	5 S		
1200			200-230/460	182T		Rigid	84.0	1.15	4.7-5.4/2.7	F	E214 	13.65	3,4,5 S	
			230/460	182T		Rigid	86.5	1.15	5.4/2.7	B	E206 	14.09	6 S	
2			3600	200-230/460	56		Cushion		1.20	6.0-5.5/2.75	B	H538	11.44	
	460/200-230	56H			Cushion		1.20	2.9/6.0-5.8	B	H844	13.94	1,2		
	460/200-230	145T			Rigid	84.0	1.15	2.7/5.9-5.4	B	E1012	14.31	5 S		
	1800	200	145T		Rigid	84.0	1.15	5.98	B	E105 	13.81	5 S		
		200-230/460	56H		Rigid		1.15	6.4-6.0/3.0	B	H181	12.19			
		200-230/460	145T		Rigid	84.0	1.15	6.0-5.2/2.6	B	E102 	13.81	5 S		
		200-230/460	145T		Rigid		1.15	6.4-6.0/3.0	B	R127	13.06	7		
		460/230	145T		Rigid	86.5	1.15	2.9/5.8	B	E1017 	16.69	6 S		
		460/200-230	56HZ		Cushion		1.15	3.5/6.6-7.0	B	H854	13.81	1,2		
		460/200-230	56HZ		Rigid		1.15	3.5/6.6-7.0	B	H886	13.81	1,2		
		575	56		Rigid		1.20	2.4	B	H965	12.19			
		575	145T		Rigid	84.0	1.15	2.08	B	E1008 	13.81	5 S		
		1200	200-230/460	184T		Rigid	85.5	1.15	6.9-7.0/3.5	F	E215 	13.65	3,4,5 S	
			230/460	184T		Rigid	87.0	1.15	7.4/3.7	B	E207 	14.09	6 S	
		3	3600	460/200-230	145T		Rigid	84.0	1.15	3.7/8.4-7.4	B	E1013	14.31	5 S
				460/200-230	56HZ		Cushion		1.15	4.3/9.0-8.6	B	H845	13.81	1,2
460/200-230	56HZ				Rigid		1.15	4.3/9.0-8.6	B	H757	13.81	1,2		
1800	200		182T		Rigid	86.5	1.15	9.8	F	E202 	13.65	5 S		
	200		182T		Rigid	88.5	1.15	9.2	F	E216 	13.65	3,6 S		
	200-208		182T		Rigid		1.15	10.0-10.0	B	R212	12.47			
	200-208		56HZ		Rigid		1.15	10.0-9.7	B	H518	14.56	1		
	208-230/460		182T		Rigid	86.5	1.15	9.7-8.4/4.2	B	E2023 	12.75			
	200-230/460		182T		Rigid	86.5	1.15	9.4-8.6/4.3	F	E226 	13.65	3,5 S		
	200-230/460		182T		Rigid	88.5	1.15	9.0-8.0/4.0	F	E217 	13.65	3,4,6 S		
	460/200-230		56HZ		Cushion		1.15	4.4/9.0-8.8	B	H855	14.56	1,2		
	460/200-230		56HZ		Rigid		1.15	4.4/9.0-8.8	B	H887	14.56	1,2		
	460/230		56HZ		Rigid		1.15	4.4/8.8	B	H539	14.56	1		
	575		182T		Rigid	86.5	1.15	3.4	F	E224 	13.65	3,5 S		
	1200		200-230/460	213T		Rigid	86.5	1.15	10.5-10.0/5.0	F	E314 	17.28	3,4,5 S	
			230/460	213T		Rigid	89.0	1.15	9.3/4.65	B	E394 	16.57	6 S	

- Notes:** 1. Sleeve Bearing
 2. Quick Connect Design Bracket, Auto Overload Protector
 3. C & D flange kit adaptable, ODP, EMI Series 850000
 4. Suitable for 200/400 V and 50 HZ
 5. S E-Plus[®] energy efficient motors complying with EPAct
 6. S E-Plus[®] 3 premium energy efficient motors surpassing EPAct
 7. Motor with automatic reset overload protector

Continued on next page

Published efficiency on tri-voltage rated motors applies at 230/460 volts. Performance at 200 or 208 volts may not be in accordance with NEMA standards. Published efficiency on 200-208 volt motors applies at 200 volts.