

3-3/8" Diameter Stock Motors

Totally Enclosed Fan & Blower Duty

Features:

- Continuous Duty, Air Over
- Dependable Quiet Sleeve Bearings
- Shaded Pole & PSC
- Single Shaft
- Totally Enclosed Construction
- 60 Hz
- 115 & 230 V

Applications: Where high humidity or dust might cause open ventilated motors to fail.
 • Vent Hood • Refrigeration Application • Electric Unit Heaters • Humidifiers • Dehumidifiers
 OEM replacement for: Nutone, Tyler, Broan, Bohn, Preway, Miami Carey, Duotherm, Ventrola, Markel, Mid-Continent, Federal Pacific, Chromalox and other fan and blower duty applications.



HP	RPM	Speeds	Volts	Amps	Stock No.	Alternate	Shaft Diameter & Length	Rotation	"A" Dim.	Iron Stack	Conn. Dia. No.	Notes
1/150	1550	1	115	.42	674		1/4-20 THD	CCWSE	2-1/2	5/8		1
1/100	1550	1	115	.38	16		1/4 x 2-1/2	CWSE	2	5/8		
1/100	1550	1	115	.38	17		1/4 x 2-1/2	CCWSE	2	5/8		
1/100	1550	1	115	.73	692	A0540	1/4 x 2-1/4	CWSE	2	5/8		2
1/100	1550	1	115	.73	693	A0541	1/4 x 2-1/4	CCWSE	2	5/8		2
1/91	1550	1	115	.4	635		1/4 x 7/8	CCWSE	2-1/8	5/8		Discontinued
1/75	1550	1	115	.6	637		1/4 x 1-3/8	CCWSE	2-1/8	5/8		1,2
1/75	1650	1	115	.50	683		1/4-20THD	CWSE	2	5/8		1
1/70	1550	1	115	.60	509	A01109	1/4 x 1-1/4	CCWSE	2-1/8	5/8		1,2
1/70	1550	1	115	.60	510		1/4 x 1	CCWSE	2-1/8	5/8		1,2
1/60-1/75	1550	2	115	.74-.50	597		5/16 x 1-1/4	CWSE	2-1/4	7/8	7u	1
1/50	1550	1	115	.75	20		1/4 x 2-1/2	CWSE	2-1/4	7/8		
1/50	1550	1	115	.75	21		1/4 x 2-1/2	CCWSE	2-1/4	7/8		
1/30	1550	1	115	.97	400		5/16 x 3-1/4	CCWSE	2-3/4	1-3/8		1
1/25	1550	1	115	1.2	431		5/16 x 2-1/2	CWSE	3	1-3/8		
1/25	1550	1	115/230	1.6/.8	9523		5/16 x 2-1/2	CWSE	3-1/8	1-3/8	11u	1
1/25	1550	1	208/230	.60	432		5/16 x 2-1/2	CWSE	3	1-3/8		
1/50-1/100	2800	2	115	.65-.44	496		1/4 x 1-1/4	CWSE	2-1/2	7/8	7u	1
1/70	3000	1	115	.62	616		1/4 x 1	CCWSE	2-1/4	5/8		2
1/60	3000	1	115	.75	983		1/4 x 2-1/4	CCWSE	2-1/4	5/8		
1/60	3000	1	115	.85	986		1/4 x 1-3/4	CWSE	2-1/4	5/8		

- Notes:**
 1. Special OEM Replacement Motor (See Pages 97-122)
 2. Supplied with Lead & Plug Assembly
 3. Item to be discontinued when stock is depleted

