


5-5/8" Diameter Stock Motors

Air Conditioners – Adapt-A-Lug® Motors Permanent Split Capacitor – 60 Hz – Continuous Duty, Air Over Thermally Protected, 3-Speed, Sleeve Bearing, Energy Efficient, 1.0 SF

OEM replacement for Chrysler, Sears, Whirlpool, Gibson, Carrier, Quiet Kool,
Delco, Singer, American Standard, Fedders, Tappan, York and others.



100, 101, 102,
104, 105, 107,
113, 114, 118,
126, 489, 482

- Lugs available separately
– See page 156
- Use Kit No. 1327 - 1/4" Slot
1328 - 3/4" Slot
1329 - Length Adapter



170, 171, 172, 173,
438, 439, 0463, 478, 479,
0511, 0544, 594,
661, 9600



OPEN LE 448, 626

Stock No.	Hp	Volts	RPM**	Amps	Speeds	Capacitor	"A"	Shaft		Connection		Notes
								Diameter	Iron Stack	Diagram No.*		
105	1/8-1/10-1/15	115	1075	2.2-1.8-1.4	3	5MFD-370V	3-1/2	9 x 1/2 x 7-1/2	1	14u	2	
100	1/8-1/10-1/15	208-230	1075	.74-.62-.50	3	5MFD-370V	3-1/2	9 x 1/2 x 7-1/2	1	14u	2	
126	1/6-1/8-1/10	115	1075	3.5-2.2-1.7	3	5MFD-370V	3-1/2	9 x 1/2 x 7-1/2	1	14u	2	
478	1/6-1/8-1/10	115	1075	2.8-2.1-1.6	3	7.5MFD-370V	3-1/2	8-1/2 x 1/2 x 7-1/2	1	14u		
118	1/6-1/8-1/10	208-230	1075	1.3-1.1-.78	3	5MFD-370V	3-1/2	9 x 1/2 x 7-1/2	1	14u	2	
438	1/6-1/8-1/10	208-230	1075	1.3-1.0-.78	3	5MFD-370V	3-1/2	9 x 1/2 x 7-1/2	1	14u		
114	1/4-1/6-1/8	115	1075	3.6-2.2-1.7	3	5MFD-370V	4	9-1/2 x 1/2 x 9-1/2	1-1/2	14u	2	
479	1/4-1/6-1/8	115	1075	3.8-2.4-2.0	3	7.5MFD-370V	4	9-1/2 x 1/2 x 9-1/2	1-1/4	14u		
113	1/4-1/6-1/8	208-230	1075	1.8-1.2-.95	3	5MFD-370V	4	10 x 1/2 x 10	1-1/4	14u	2	
439	1/4-1/6-1/8	208-230	1075	1.8-1.2-.95	3	5MFD-370V	4	7-1/2 x 1/2 x 8-1/2	1-1/4	14u		
0511	1/4-1/6-1/8	208-230	1075	1.8-1.2-1.0	3	5MFD-370V	4	7 x 1/2 x 7	1-1/4	14u		
626	1/4-1/6-1/8	277	1075	1.3-.87-.67	3	5MFD-370V	4-1/4	7-7/8 x 1/2 x 7-7/8	1-1/2	14u		
101	1/3-1/4-1/6	115	1075	5.6-3.9-3.0	3	5MFD-370V	4-1/4	6-3/4 x 1/2 x 7	1-3/4	14u	2	
102	1/3-1/4-1/6	208-230	1075	2.6-1.9-1.5	3	5MFD-370V	4-1/4	6-3/4 x 1/2 x 7	1-3/4	14u	2	
0463	1/3-1/4-1/5	208-230	1075	2.3-1.6-1.3	3	5MFD-370V	4	7 x 1/2 x 7	1-1/2	14u		
448	1/3-1/4-1/6	277	1075	1.9-1.4-.85	3	7.5MFD-370V	4-3/4	7-5/8 x 1/2 x 7-5/8	1-3/4	14u		
594	1/2-1/3-1/4	115	1075	7.3-5.6-4.0	3	10MFD-370V	5-1/4	7-1/2 x 1/2 x 7-1/2	2-1/2	14u		
107	1/2-1/3-1/4	208-230	1075	3.2-2.0-1.5	3	7.5MFD-370V	5	8 x 1/2 x 8	2-1/4	14u	2	
0544	1/2-1/3-1/4	208-230	1075	3.2-2.0-1.5	3	7.5MFD-370V	5	7 x 1/2 x 7	2-1/4	14u		
9600	3/4-1/2-1/3	115	1075	12.6-8.8-6.6	3	10MFD-370V	5-1/2	8 x 1/2 x 8	2-1/2	14u		
489	3/4-1/2-1/3	208-230	1075	4.6-3.5-2.0	3	10MFD-370V	5-1/4	7 x 1/2 x 7-1/4	2-1/2	14u	2	
170	1/6-1/10-1/15	208-230	1625	1.1-.54-.40	3	5MFD-370V	3-3/4	8-1/2 x 1/2 x 8-1/2	1	14u	1	
661	1/4-1/6-1/8	115	1625	3.3-2.5-2.0	3	5MFD-370V	4	8-1/2 x 1/2 x 8-1/2	1-1/4	14u		
171	1/4-1/6-1/8	208-230	1625	1.7-1.0-.74	3	5MFD-370V	4-1/4	8-1/2 x 1/2 x 8-1/2	1-1/4	14u		
104	1/3-1/4-1/6	115	1625	4.3-3.1-2.5	3	5MFD-370V	4-1/4	8-5/8 x 1/2 x 8-5/8	1-1/2	14u	2	
172	1/3-1/4-1/6	208-230	1625	2.5-1.5-1.1	3	5MFD-370V	4-1/2	8-1/2 x 1/2 x 8-1/2	1-1/2	14u		
173	1/2-1/3-1/4	208-230	1625	3.8-2.7-2.2	3	5MFD-370V	5	8-1/2 x 1/2 x 8-1/2	2	14u		
482	3/4-1/2-1/3	208-230	1625	4.2-3.0-2.0	3	7.5MFD-370V	5-1/4	7-1/2 x 1/2 x 7-1/2	2-1/2	14u	2	

- Notes:
1. Special OEM Replacement Motor (See Pages 97-122)
2. Mounting Accessories Packaged with Motor
*See Pages 160-163 for Connection Diagram
**Approx 150 rpm between speeds