


# 5-5/8" Diameter Outdoor Sleeve Bearing Fan Motors

## Condensers - Heat Pump - Refrigeration

### Features

- Auto Protector
- Class "B" Insulation
- Closed Except Lead End
- Energy Efficient S
- Ex. Thrubolt, Sh. End
- Reversing Plug
- Shaft Slinger
- Sleeve Bearing
- PSC
- Vert. Shaft Up or Horiz. Mount
- 1/2" Dia. Shaft - Dbl. Flat
- 6 & 8 Pole
- 26" Leads
- 48 Frame (5-5/8" Dia.)
- 60° C Max. Ambient
- 60 HZ




### "CONSERVATIONIST" (CAPACITOR NOT INCLUDED)

HP	RPM/ Speeds	Volts	Amps Rated	Amps Max.	Stock Number	Capac.	Dim. Ref.	Conn. Dia.	Notes
1/6	1075/750	208-230	.9	1.1	<b>FS1016</b>	5/370V	1	16	S
1/4	1075/750	208-230	1.4	2.0	<b>FS1026</b>	5/370V	2	16	S
1/4	1075	208-230	1.5	1.9	<b>FS1026S</b>	5/370V	3	17	1 S
1/4	1625	208-230	1.4	1.8	<b>FS1024S</b>	5/370V	12	64	1 S
1/3	1075/750	208-230	1.7	2.6	<b>FS1036</b>	7.5/370V	4	16	S
1/3	1075	208-230	2.5	3.3	<b>FS1036S</b>	5/370V	5	17	S
1/3	1075	208-230	1.9	2.6	<b>FS1037S</b>	5/370V	6	17	1 S
1/2	1075/750	208-230	2.5	3.6	<b>FS1056</b>	10/370V	10	16	S
1/2	1075	208-230	3.6	4.4	<b>FS1056S</b>	5/370V	7	17	1 S
3/4	1075	208-230	4.0	5.0	<b>FS1076S</b>	10/370V	8	17	S

HP	RPM/ Speeds	Volts	Amps Rated	Amps Max.	Stock Number	Capac.	Dim. Ref.	Conn. Dia.	Notes
1/6	825/2	208-230	.9	1.3	<b>FS1018</b>	5/370V	11	16	S
1/4	825/2	208-230	1.5	1.9	<b>FS1028</b>	7.5/370V	9	16	S
1/3	825/2	208-230	1.8	2.5	<b>FS1038</b>	12.5/370V	8	16	S

#### Notes:

- Resilient rings included for refrigeration applications



### Approximate Dimensions

Ref.	BM	C	N
1	3-13/16	10-1/4	6-7/16
2	4-3/16	10-5/8	6-7/16
3	3-15/16	10-3/8	6-7/16
4	4-13/16	11-1/4	6-7/16
5	4-3/8	10-3/4	6-7/16
6	4-3/16	10-5/8	6-7/16
7	5-3/16	11-5/8	6-7/16
8	5-5/8	12	6-7/16
9	5-1/16	11-1/2	6-7/16
10	5-1/16	11-9/16	6-7/16
11	4-9/16	11	6-7/16
12	4	8-15/16	4-15/16