


**48 Frame Open Lead End Vertical Condenser Fan Motors**  
**Permanent Split Capacitor – Energy Efficient, Electrically Reversible**  
**1.0 SF – Sleeve & Ball Bearing – Continuous Duty, Air Over**  
**60°C Ambient – 60 Hz – Thermally Protected**

**Features:** Drain Holes with Plugs Each End  
 • Continuous Duty, Air Over • Water Slinger on Shaft  
**Application:** For Condenser Fans and Heat Pumps



**Open Opposite Shaft End**  
 Shaft Up, Horizontal



**Dripproof Open Opposite Shaft End**  
 Shaft Up, Horizontal

**OPEN OPPOSITE SHAFT END – VERTICAL SHAFT UP/HORIZONTAL**

Stock No.	Hp	Volts	RPM**	Amps	Speeds	Capacitor	"A"	Shaft Diameter & Length	Iron Stack	Connection Diagram No.*	Notes
474	1/4	208-230	825	1.7	1	7.5MFD-370V	5	1/2 x 6	2	17u	
9423	1/3	115	825	5.4	1	15MFD-370V	5-3/4	1/2 x 6	2-3/4	17u	
475	1/3	208-230	825	2.0	1	10MFD-370V	5-1/4	1/2 x 6	2-1/2	17u	
476	1/3	208-230	825	2.0	1	10MFD-370V	5-1/4	1/2 x 6	2-1/2	17u	2
786	1/3	460	825	1.4	1	10MFD-370V	6-1/2	1/2 x 6	2-3/4	17u	2,5
477	1/2	208-230	825	3.3	1	10MFD-370V	5-3/4	1/2 x 6	2-3/4	17u	2
787	1/2	460	825	2.1	1	10MFD-370V	7-1/4	1/2 x 6	3-1/2	17u	2,5
0500	1/4	208-230	1075	1.4	1	7.5MFD-370V	3-3/4	1/2 x 6-1/2	1-1/4	35u	
735	1/4	208-230	1075	2.1	1	5MFD-370V	3-3/4	1/2 x 6-1/2	1-1/4	35u	3
0675	1/4	208-230	1075	1.4	1	7.5MFD-370V	3-3/4	1/2 x 6	1-1/4	35u	2
0501	1/3	208-230	1075	1.9	1	7.5MFD-370V	4	1/2 x 6-1/2	1-1/2	35u	
736	1/3	208-230	1075	3.0	1	5MFD-370V	4	1/2 x 6-1/2	1-1/2	35u	3
0676	1/3	208-230	1075	1.9	1	7.5MFD-370V	4	1/2 x 6	1-1/2	35u	2
784	1/3	460	1075	1.3	1	5MFD-370V	5-1/2	1/2 x 6	1-3/4	35u	
0502	1/2	208-230	1075	2.9	1	10MFD-370V	4-3/4	1/2 x 6-1/2	2	35u	
737	1/2	208-230	1075	4.2	1	7.5MFD-370V	4-3/4	1/2 x 6-1/2	2	35u	3
0677	1/2	208-230	1075	2.9	1	10MFD-370V	4-3/4	1/2 x 6	2	35u	2
785	1/2	460	1075	1.8	1	7.5MFD-370V	5-3/4	1/2 x 6	2	35u	
9426	1/2	575	1075	1.3	1	FURNISHED	5-1/4	1/2 x 4-3/4	2-1/4	17u	2
0527	3/4	208-230	1075	4.5	1	15MFD-370V	5-1/4	1/2 x 6-1/2	2-1/2	35u	2
738	3/4	208-230	1075	5.4	1	10MFD-370V	5-1/4	1/2 x 6	2-1/2	17u	3
545	3/4-1/2	208-230	1075	4.3-3.1	2	15MFD-370V	5-1/4	1/2 x 6	2-1/2	41u	2
792	3/4	460	1075	2.6	1	10MFD-370V	5-3/4	1/2 x 6	2-1/2	35u	
9427	3/4	575	1075	2.1	1	FURNISHED	6-1/4	1/2 x 4-3/4	3-1/2	17u	2
782	1/4-1/5	460	1625	.93-.89	2	5MFD-370V	4-3/4	1/2 x 6	1-1/2	98u	2,5
783	1/2-1/3	460	1625	1.6-1.2	2	7.5MFD-370V	5-3/4	1/2 x 6	2-1/4	98u	2,5
9425	1/2	575	1625	1.2	1	FURNISHED	5-1/2	1/2 x 4-3/4	2	17u	2

**DRIPPROOF – VERTICAL SHAFT UP/HORIZONTAL**

Stock No.	Hp	Volts	RPM**	Amps	Speeds	Capacitor	"A"	Shaft Diameter & Length	Iron Stack	Connection Diagram No.*	Notes
9613	1/4	460	1075	1.3	1	5MFD-370V	4-1/4	1/2 x 6	1-1/4	17u	2,3,4
436A	1/3	460	1075	1.0	1	5MFD-370V	4-3/4	1/2 x 6	1-3/4	17u	1,2,3,4
435A	1/2	460	1075	1.7	1	7.5MFD-370V	5	1/2 x 6	2	17u	1,2,3,4
158A	3/4	460	1075	2.2	1	10MFD-370V	5-1/2	1/2 x 6	2-1/2	17u	2,3,4
456	1/4	208-230	1625	1.5	1	5MFD-370V	4	1/2 x 8	1-1/4	17u	3,4 discontinued see FS1024S
665	1/3	208-230	1625	2.0	1	5MFD-370V	4-1/4	1/2 x 6	1-1/2	17u	3,4
666A	1/2	208-230	1625	3.8	1	5MFD-370V	4-3/4	1/2 x 6	2	17u	3,4
461	1/2-1/3-1/4	208-230	1625	3.8-2.7-2.3	3	5MFD-370V	4-3/4	1/2 x 6	2	18u	3,4 discontinued see FD1054
159A	1	208/460	1075	5.0/2.5	1	15MFD-370V	5-3/4	1/2 x 6	2-1/2	147u	2,3,4

**Notes:** 1. Special OEM Replacement Motor (See Pages 97-122) 2. Ball Bearings 3. Has HEX mounting hub on both ends for cradle base mounting  
 4. Resilient Mounting Rings Included 5. Includes conduit box, mounting screws, gasket, shipped detached  
 \*See Pages 160-163 for Connection Diagram \*\*Approx 150 rpm between speeds