

5-5/8" Diameter Totally Enclosed Outdoor Ball Bearing Fan Motors

Condensers - Heat Pump - Refrigeration

Features

- All Angle Mount
- Auto Protector
- Class "B" Insulation
- Energy Efficient s
- Ext. Thru Bolts - Both Ends
- Permanent Split Capacitor
- Reversing Plug
- 1/2" Dia. Shaft - Dbl. Flat
- 26" Leads (min.)
- 48 Frame (5-5/8" Dia.)
- 60° C Ambient
- 60 HZ



"CONSERVATIONIST" "TURN-A-BOU" 1 AND 2-SPEED (CAPACITOR NOT INCLUDED)

HP	RPM/ Speeds	Volts	Amps		Stock Number	Capac.	Dim. Ref.	Conn. Dia.	Notes	
			Rated	Max.						
1/10	825	208-230	0.6	0.63	FE1008SVI	5/370V	1	17	2	S
1/8	825	208-230	0.8	0.9	FE1008S	5/370V	1	17	2	S
1/6	825	208-230	1.1	1.6	FE1018S	5/370V	1	17	2	S
1/6	1075	208-230	.9	1.3	FE1016S	5/370V	1	17		S
1/4	825	208-230	1.5	1.9	FE1028S	5/370V	14	17	2	S
1/4	1075	208-230	1.3	1.8	FE1026S	5/370V	2	17		S
1/4	1075/2	208-230	1.3	1.8	FE1026	5/370V	3	16		S
1/4	1075	460	.65	.9	FEH1026S	7.5/370V	4	17		S
1/4	850	460	.75		FEH1028S	5/370V	20	17	2	S
1/3	825	208-230	1.8	2.4	FE1038S	7.5/370V	5	17	2	S
1/3	1075	208-230	1.8	2.8	FE1036S	7.5/370V	5	17		S
1/3	1075/2	208-230	1.8	2.8	FE1036	7.5/370V	6	16		S
1/3	1075	460	.8	1.15	FEH1036S	7.5/370V	7	17		S
1/3	1075	575	.75	.8	5FE1036S	7.5/440V	15	64		S
1/2	825	208-230	2.7	3.7	FE1058S	10/370V	8	17	2	S
1/2	1075	208-230	2.8	3.5	FE1056S	10/370V	8	17		S
1/2	1075/2	208-230	2.8	3.5	FE1056	10/370V	9	16		S
1/2	1075	460	1.2	1.35	FEH1056SVI	10/370V	10	65	2	S
1/2	1075	460	1.2	1.35	FEH001	10/370V	19	65	2	S
1/2	1075	575	1.1	1.2	5FE1056S	7.5/370V	16	64		S
1/2	1625	575	1.0	1.4	5FE1054S	7.5/440V	15	64		S
3/4	1075	208-230	3.8	4.7	FE1076S	12.5/370V	11	17		S
3/4	1075/2	460	1.7	1.9	FEH1076	10/370V	12	16	1	S
3/4	1075	460	1.7	1.9	FEH1076S	10/370V	13	17		S
3/4	1075	575	1.8	1.9	5FE1076S	15/370V	17	64		S

Notes:

1. Lo-speed 1/2 HP
2. 1/2" hub on shaft end and slinger

Approximate Dimensions

Ref.	BM	C	N
1	4	10	6
2	4-5/8	10-5/8	6
3	4-3/8	10-3/8	6
4	4-3/4	10-3/4	6
5	5-1/8	11-1/8	6
6	5-1/16	11-1/16	6
7	5-1/4	11-1/4	6
8	5-5/8	11-5/8	6
9	5-9/16	11-9/16	6
10	5-9/16	11-9/16	6
11	5-7/8	11-7/8	6
12	6-1/16	12-1/16	6
13	6-1/8	12-1/8	6
14	4-11/16	10-11/16	6
15	5-3/8	11-7/8	6-1/2
16	5-5/8	12-1/8	6-1/2
17	6-1/8	12-5/8	6-1/2
18	4-1/4	10-1/4	6
19	5-9/16	9-9/16	4
20	4-7/8	10-7/8	6

