

Features

- Shaded Pole
- UL & CSA Listed
- 1/4" x 20 Threaded Shaft
- 60 HZ
- 1550 RPM



TOTALLY ENCLOSED CAST IRON

Watts	Volts	Amps	Stock Number	Equivalent	Rotation	Industry No.
4	115	0.29	UB04CWL	232	CWLE	5211
4	115	0.29	UB04CCL	233	CCWLE	5212
4	230	0.14	UB04CWH	234	CWLE	5221
4	230	0.14	UB04CCH	235	CCWLE	5222
6	115	0.36	UB06CWL	236	CWLE	5311
6	115	0.36	UB06CCL	237	CCWLE	5312
9	115	0.53	UB09CWL	238	CWLE	5411
9	115	0.53	UB09CCL	239	CCWLE	5412
9	230	0.27	UB09CWH	240	CWLE	5421
9	230	0.27	UB09CCH	241	CCWLE	5422
16	115	0.80	UB16CWL V1	242	CWLE	5811
16	115	0.80	UB16CCL V1	243	CCWLE	5812
16	230	0.40	UB16CWH V1	244	CWLE	5821
16	230	0.40	UB16CCH V1	245	CCWLE	5822

Note:

Each motor supplied with Neoprene Silencer, Speed Nut & Mounting Screws. Single Foot Mount.

TOTALLY ENCLOSED ALUMINUM

Watts	Volts	Amps	Stock Number	Equivalent	Rotation	Industry No.
2	115	0.34	UB02CWLA	220	CWLE	5109
4	115	0.40	UB04CWLA	221	CWLE	5213
4	115	0.40	UB04CCLA	222	CCWLE	5214
6	115	0.50	UB06CWLA	225	CWLE	5313
6	115	0.50	UB06CCLA	226	CCWLE	5314
9	115	0.58	UB09CWLA	227	CWLE	5413
9	115	0.58	UB09CCLA	228	CCWLE	5414
9	230	0.29	UB09CWA	229	CWLE	5423
9	230	0.29	UB09CHA	230	CCWLE	5424

Note:

Each motor supplied with Neoprene Silencer, Speed Nut & Mounting Screws. One Foot Mount on all stock numbers except UB02CWLA has none.