



**Fig. A D6002, D6004, D6006**



**Fig. B D6082, D6084, D6066, D6086**



**Fig. C D6068, D6088, D6070, D6073, D6090, D6093**

NEMA 48 FRAME SPLIT PHASE BELTED FAN & BLOWER MOTORS RESILIENT BASE • OPEN DRIP PROOF • CONTINUOUS DUTY 115/230 VOLT • BALL BEARING • REVERSIBLE								
H.P.	RPM	FLA	Service Factor	Thermal Protection	Fig.	Model	Shaft Dim.	Ring to Ring Dim.
1/4	1725	5.2/2.6	1.35	Auto	A	D6002	1/2 x 1 1/2	7.435
1/3	1725	6.2/3.1	1.35	Auto	A	D6004	1/2 x 1 1/2	7.935
1/2	1725	8.6/4.3	1.25	Auto	A	D6006	1/2 x 1 1/2	8.435

NEMA 56 FRAME CAPACITOR START MOTORS 115/208-230 VOLT • RESILIENT BASE • BALL BEARING CONTINUOUS DUTY • REVERSIBLE • UL & CSA CERTIFIED								
H.P.	RPM	FLA	Service Factor	Thermal Protection	Fig.	Model	Shaft Dim.	Ring to Ring Dim.
1/3	1725	6.2/3.1	1.35	Auto	B	D6082	5/8 x 2	7.945
1/2	1725	8.8/4.4	1.25	Auto	B	D6084	5/8 x 2	8.445
3/4	3450	9.6/4.8	1.25	Auto	B	D6066	5/8 x 2	9.445
3/4	1725	10.8/5.4	1.25	Auto	B	D6086	5/8 x 2	9.445
1	3450	12.0/6.0	1.25	Auto	C	D6068	5/8 x 2	9.445
1	1725	12.8/6.4	1.15	Auto	C	D6088	5/8 x 2	9.445
1 1/2	3450	17.2/8.6	1.15	Auto	C	D6070	5/8 x 2	9.445
1 1/2	1725	14.4/7.2	1.15	Auto	C	D6090*	5/8 x 2	10.445
2	3450	24.0/12.0	1.15	Auto	C	D6073	5/8 x 2	10.445
2	1725	20.0/10.0	1.15	Auto	C	D6093*	5/8 x 2	10.945

\* 56H Mounting

Products on this page are NOT SUITABLE for unattended equipment unless indicated by ► symbol. See inside back cover for additional information.